

ACCESSORIES • Mastics & Nails







ACCESSORIES • Mastics & Nails

• Shingle Stick®

is an elastomeric bitumen based mastic and has a lasting plasticity.

 The surface should be clean, dust free, degreased and free from loose particles SHINGLE STICK may be applied on slightly damp surfaces.

 When the slope of the roof is greater than 60° or where the shingles are exposed to low temperatures, violent winds or are in the shade, provide extra adhesion with blobs of SHINGLE STICK (25mm diameter, 1mm thick).


(* Registered average values)

Shingle Stick*		Plastal Stick [®]	Plastal [°]	
			PLAST	
	Black	Black	Black	

• Plastal Stick® and Plastal®

are oxidised bitumen based mastics.

Colour	Black	Black	Black
Density at 20°C	± 1,2 kg/l	± 1,2 kg/l	± 1,2 kg/l
Drying time – RH 50–60 % – touch dry	± 24 h	± 24 h	± 24 h
Flash point	± 24° C	± 24° C	± 24° C
Temperature resistance	from - 20 to 80 °C	from - 20 to 80 °C	from – 20 to 80 °C
Application	from 0 to 40 ℃	from 0 to 40 °C	from 0 to 40 °C
Packaging	310 ml (12 pc./box)	310 ml (12 pc./box)	5 kg
	3 m	20 July 10 Jul	J. 100 J.



• IKO Nails®

are hot galvanised extra large head professional steel wire roofing nails.

	Galvanised nails	Galvanised nails > refill
	ACO CARROLL SPECIAL TO	
Diameter shaft	2,7 mm	2,7 mm
Diameter head	≥ 9 mm	≥ 9 mm
Length	20, 25, 30, 35 mm	20, 25, 30, 35 mm
Zinc coating	300 g/m ²	300 g/m ²
Packaging	5 kg (1 kg = $\pm 560 \text{ pc.}$)	5 kg (1 kg = \pm 560 pc.)
	10 x 0 x 0 x 0	

(* Registered average values)







